

DESCRIPTIONS


4mm² H1Z2Z2-K Solar Cable TÜV 1500V, for photovoltaic power Direct Current (DC) .

STANDARDS

TÜV EN50618 **H1Z2Z2-K** file No.: R 50546675 & **IEC62930** file No.: R 50546688

CABLE CONSTRUCTION

Drawing:



- **Conductor**

Size4mm²

Stranding56*0.285 ± 0.005mm

Diameter2.6mm ± 0.04mm
- **Insulation**

XLPO, electron-beam cross-linked, LSHF

Thickness0.7mm ± 0.04mm

ColorBlack 
- **Jacket**

XLPO, electron-beam cross-linked, LSHF

Thickness0.8mm ± 0.04mm

ColorBlack  or Red 

Outer Diameter: 5.6mm ± 0.2mm

MECHANICAL FEATURE

- Minimum Bending radius

Fixed: 4 x Overall Diameter; Flexing: 5 x Overall Diameter
- Temperature range

-40 °C to +90 °C, Max. temp. at conductor +120 °C
- Weather /UV resistance

EN 50289-4-17
- Ozone resistance

EN 50396, cl. 8.1.3
- Halogen free

EN 60754-1
- Flame-resistant test

EN 60332-1-2
- Short circuit temperature

250°C for 5 s
- Anticipated service life

30 years
- Approvals

EN50618 H1Z2Z2-K & IEC62930

ELECTRICAL PARAMETER

- Rated voltage

DC: 1.5/1.5kV; AC: 1.0/1.0 kV
- Conductor Resistance at 20°C

≤ 5.09 Ω/km
- Test Voltage (AC)

AC 6.5kV, 50Hz, 5 min
- Max. permitted voltage 1.8kV DC
- Min. Insulation resistance at 20°C 580MΩ/KM
- Spark test AC 10kV

■ Current carrying capacity at 120 °C (Ambient temperature 60 °C):

Condition	Exposed 	On surfaces without contact 	On surfaces with contact 	In conduit, pipe, duct 
Current carrying capacity/ A	55	52	44	33

Printing & Packing

- Printing: SHANGHAI KUKA CABLE H1Z2Z2-K EN50618 & 62930 IEC 131 1X4mm² 1500V DC XLPO/XLPO HALOGEN FREE LOW SMOKE SOLAR CABLE+ + Meter mark
- Packing: 500M/roll, 27rolls/pallet, 20pallets/20FCL (270KM)
- Customized printing and delivering in other ways.